Shenzhen QOHO Electronics Co., Ltd



Mobile DVR accessories



Key Features

Waterproof and vandal proof UPS

The UPS is high-end backup power which designed for vehicle MDVR products.

It can support 1 to 2 hours after power off.

The input section uses a lithium iron phosphate battery and special charge management IC;

and it uses the high efficiency DC-DC buck-boost switching circuit.

In order to achieve accurate voltage overshoot, over-discharge voltage,

current overload and short circuit protection it uses a battery cell Protection control circuit.

Rated input voltage is 8 ~ 36V DC. When the supply voltage of vehicle MDVR is less than 9V or unexpected power failure the vehicle MDVR will automatically switch to UPS.

Caution: MDVR will work five minutes default after the vehicle keys close,

if customers want to lengthen working hours after power failure,

please change the delay time on the DATE&TIME interface of MDVR.

IC control technology and multiple protection circuit;

Tel: 0086-755-88832758 **Fax:** 0086-755-61624570 **Website**: www.gohovisions.com

Email: sales@qohocctv.com Skype: qohocctv : qohovisions

Factory Address: 12/F,C area, HuiLongDa Industrial Park,Shiyan street,

Baoan district, Shenzhen city, Guangdong province, China.





Specification

Projects	Technical indicators	Unit	Remark	
working temperature	-20~75°C	°C		
vibration resistance	MIL-STD- 810F	°C		
power performance	ISO 7637			
shock limit	≤2000	G	(19,600M/S2)@1MS	
waterproof rating	IP53			
machine power	0.01	W		
cooling	metal cooling		natural cooling	
Input Characteristics				
Projects	Technical Requirements	Unit	Remark	
Input voltage	8V~36V	Vdc		
Conversion efficiency	≥85%			
Maximum input current	≤2.6	A	12V below	
Output Characteristics				
Projects	Technical Requirements	Unit	Remark	
Output Current Range	0~1.4	A		
Output Voltage Range	8~9.7	V		
Noise	≤50	dB		
Protection Characteristics				
Project	Technical Requirements	Unit	Remark	
Discharge voltage protection (batteries)	-	V	Over discharge release 7V	
Charging voltage protection (batteries)	10.9	V	Overcharge release 10.95V	
Load current (batteries)	≥1	A		
Output over-current	≥6	A	Lock(protection)	


Email: sales@qohocctv.com **Skype:** qohocctv : qohovisions


Factory Address: 12/F,C area, HuiLongDa Industrial Park,Shiyan street,

Baoan district, Shenzhen city, Guangdong province, China.










Tel: 0086-755-88832758 **Fax:** 0086-755-61624570 **Website**: www.qohovisions.com

Email: sales@qohocctv.com Skype: qohocctv: qohovisions

Factory Address: 12/F,C area, HuiLongDa Industrial Park,Shiyan street,







This Product can work with:

8ch H.265	8ch 1080P Mobile	4ch AHD + 4ch	4ch single SD
Mobile DVR	DVR	IPC Mobile DVR	Card MDVR

Email: sales@qohocctv.com **Skype:** qohocctv : qohovisions

Factory Address: 12/F,C area, HuiLongDa Industrial Park,Shiyan street,

Baoan district, Shenzhen city, Guangdong province, China.

